

# P4 Outdoor Fixed LED Display

MW7840-FO-D



## Features

- Supports adjusting the brightness.
- High refresh rate, high brightness, wide viewing angle, no glare, and low attenuation offer better visual experience.
- High grayscale image delivers more details.
- Supports 360° arc splicing screen. Supports naked-eye 3D display.
- Aluminum alloy cabinet, each only weights 24.5kg.
- The modular design of the whole device supports complete front and rear maintenance, efficient and convenient.
- The module uses aluminum alloy casing, with better thermal stability and heat dissipation.
- CNC precision machining achieves high dimensional accuracy and good flatness.
- IP65 rating can withstand harsh outdoor environment.

## Specifications

Module	Description
Pixel Pitch	P4.0

Module Resolution (W*H)	40*240
Module Dimensions (mm)	160*960
<b>Cabinet</b>	<b>Description</b>
Cabinet Dimensions (W*H*D) (mm)	960*960*76
Cabinet Resolution (W*H)	240*240
Material	Aluminium Profile
<b>Processing Image</b>	<b>Description</b>
Single Pixel Brightness Correction	Support
Single Pixel Color Correction	Support
Brightness (nits)	6000
Color Temperature (K)	2000 to 9500
Viewing Angle (H/V)	160° /140°
Center Distance Deviation of LED	<3%
Brightness Uniformity	≥95%
Color Uniformity (Cx,Cy)	±0.003Cx,Cy
Contrast Ratio	5000: 1
<b>Processing performance</b>	<b>Description</b>
Pixel Density (pitch/m <sup>2</sup> )	62500
Grayscale	14bit
Scanning Mode	10S
Drive Mode	Constant current driving
Refresh Rate (Hz)	3840
<b>Electrical</b>	<b>Description</b>
Power Supply	AC 100 to 240V
Average Power Consumption (W/m <sup>2</sup> )	280
Max. Power Consumption (W/m <sup>2</sup> )	850
<b>General</b>	<b>Description</b>
Maintenance Mode	rear maintenance
Ingress Protection	IP65
Weight (Kg/pcs)	24.5
Operation Temperature	-20° C to +50° C
Operating Humidity	10% to 90%RH, non-condensing
Storage Temperature	-30° C to +60° C
Storage Humidity	10% to 95%RH, non-condensing
LED lifetime (h)	100000

**Zhejiang Uniview Technologies Co., Ltd.**

No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China

Email: [overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)

<http://www.uniview.com>

©2023 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.